

Product data sheet

Slimdrive EMD-F



Electromechanical swing door drive for single leaf fire and smoke protection doors

AREAS OF APPLICATION

- Fire and smoke protection doors
- Single-action, single leaf, right and left closing doors
- Single-action doors up to 1400 mm leaf width or 230 kg weight
- Interior and exterior doors with high access frequency
- Door leaf installation and transom installation



PRODUCT FEATURES

- Closing force with variable adjustment of EN 4-6
- Opening and closing speed can be individually adjusted
- Mechanical latching action when operated without current, and electrical latching action in regular operation, which accelerates the door shortly before the closed position
- Low-energy function opens and closes the door with reduced speed, fulfilling the highest safety demands
- Servo function for motorized support when manually opening the door
- Vestibule function controls the opening and closing of two consecutive doors (interlocking door system)
- Obstacle detection detects an object through contact and stops the opening or closing process
- Automatic reversing detects an obstacle and returns to the opening position
- Push & Go function triggers the automatic drive following light manual pressure on the door leaf
- Drive can be used with roller guide rail or link arm

TECHNICAL DATA

Productname	Slimdrive EMD-F
Height	70 mm
Depth	121 mm
Leaf weight (max.) 1-leaf	230 kg
Hinge clearance (min.-max.) 2-leaf	1500 mm - 2800 mm
Leaf width (min.-max.)	750 mm - 1400 mm
Reveal depth (max.)	400 mm
Door overlap (max.)	30 mm
Drive type	Electromechanical
Opening angle (max.)	130 °
Spring pre-load	EN4 - EN6
DIN left	Yes
DIN right	Yes
Transom installation opposite hinge side with link arm	Yes
Transom installation opposite hinge side with roller guide rail	Yes
Transom installation hinge side with roller guide rail	Yes
Door leaf installation hinge side with roller guide rail	Yes
Mechanical latching action	Yes
Electrical latching action	Yes
Electrical closing sequence control	Yes
Disconnection from mains	Main switch in the drive
Activation delay (max.)	20 s
Operating voltage	230 V
Power rating	230 W
Power supply for external consumers (24 V DC)	1000 mA

Service temperature	-15 °C - 50 °C
IP rating	IP20
Mode of operation	Off, Automatic, Permanently open, Shop closing, Night
Type of function	Fully automatic
Automatic function	Yes
Low-energy function	Yes
Servo function	Yes
Key function	Yes
Vestibule function	Yes
Obstacle detection	Yes
Automatic reversing	Yes
Push & Go	adjustable
Operation	Programme switch DPS, Programme switch integrated in the drive
Parameter setting	GEZEconnects (PC + Bluetooth), ST 220 service terminal
Approvals	DIN 18650, DIN 18263-4, EN 16005
Suitability for fire protection doors	Yes

VARIANTS / ORDER INFO

Name	Description	Ident-No.	Supply voltage	Operating voltage	Leaf width (min.)
Slimdrive EMD-F	Electro-mechanical swing door drive for 1- and 2-leaf single-action doors and fire protection doors	107577	230 V	230 V	750 mm

ACCESSORY**GC 342**

Laser scanner for the protection of automatic swing doors and windows with integrated object and wall blanking



Name	Description	Ident-No.	Colour	Dimensions	Operating voltage
GC 342 (left module)	consisting of sensor module, cable and accessories	167433	white RAL 9016	143 x 86 x 40 mm	24 V
GC 342 (right module)	consisting of sensor module, cable and accessories	167435	black	143 x 86 x 40 mm	24 V
GC 342 (left module)	consisting of sensor module, cable and accessories	167434	stainless steel optic	143 x 86 x 40 mm	24 V
GC 342 (left module)	consisting of sensor module, cable and accessories	167432	black	143 x 86 x 40 mm	24 V
GC 342 Kit	comprising two sensors for securing the swivelling range of automatic swing doors in accordance with DIN 18650 / EN 16005	167439	white RAL 9016	143 x 86 x 40 mm	24 V

Slimdrive EMD-F



Name	Description	Ident- No.	Colour	Dimensions	Operating voltage
GC 342 (right module)	consisting of sensor module, cable and accessories	167437	stainless steel optic	143 x 86 x 40 mm	24 V
GC 342 Kit	comprising two sensors for securing the swivelling range of automatic swing doors in accordance with DIN 18650 / EN 16005	167438	black	143 x 86 x 40 mm	24 V
GC 342 (right module)	consisting of sensor module, cable and accessories	167436	white RAL 9016	143 x 86 x 40 mm	24 V
GC 342 Kit	comprising two sensors for securing the swivelling range of automatic swing doors in accordance with DIN 18650 / EN 16005	167440	stainless steel optic	143 x 86 x 40 mm	24 V
