

# Product data sheet

# Link arms TS 4000 / 2000



with mechanical holding open

#### AREAS OF APPLICATION

- To hold open non-fire protection doors
- Right and left single-action doors

## PRODUCT FEATURES

→ Can be used up to 70 mm reveal depth with transom installation

## TECHNICAL DATA

Productname	Link arms TS 4000 / 2000
Hold-open device	Mechanical
Hold-open device can be overridden	Yes
Hold-open point	70 ° - 150 °

## VARIANTS / ORDER INFO

Name	Description	Ident-No.	Colour	Hold-open device single-action	Hold-open point max.
Link arms TS 4000/2000 / F	with mechanical holding open	102454	silver-coloured	70 °	150 °
Link arms TS 4000/2000 / F	with mechanical holding open	102456	white RAL 9016	70 °	150 °
Link arms TS 4000/2000 / F	with mechanical holding open	102457	acc. to RAL	70 °	150 °

## INSTALLATION MATERIAL

### MOUNTING PLATE LINK ARM

For TS 4000/TS 2000, with slim frames



Name	Description	Ident-No.	Colour
Mounting plate link arm	for TS 4000/TS 2000, with slim frames	082506	acc. to RAL
Mounting plate link arm	for TS 4000/TS 2000, with slim frames	057109	silver-coloured

# Link arms TS 4000 / 2000



## MOUNTING PLATE LINK ARM

For TS 4000/TS 2000 for parallel arm installation



Name	Description	Ident-No.	Colour
Mounting plate link arm	for TS 4000/TS 2000, for parallel arm installation	053319	dark bronze
Mounting plate link arm	for TS 4000/TS 2000, for parallel arm installation	027460	acc. to RAL
Mounting plate link arm	for TS 4000/TS 2000, for parallel arm installation	053318	silver-coloured