

# Product data sheet

## SCT 222 \*



Key switch for authorised activation and changing the mode of operation of automatic doors, surface and flush-mounted

### AREAS OF APPLICATION

- Authorised control of operating statuses on various GEZE products
- Approved for use with GEZE emergency exit system door control units
- Designed for Euro profile half cylinder 30/10
- Outdoors thanks to high IP rating



### PRODUCT FEATURES

- With integrated LED display for status feedback
- Right LED red/green and left LED yellow
- High-quality aluminium front plate
- Two-sided switching operation, with Euro profile half cylinder and three keys
- Sabotage-proof design, can only be opened with key

### TECHNICAL DATA

Productname	SCT 222 *
IP rating	IP54
Type of installation	Surface-mounted installation, Flush-mounted installation
Material	Aluminum

### VARIANTS / ORDER INFO

Designation	Description	Ident-No.	Colour	Dimensions	Type of installation
SCT 222 key switch with LEDs *	Two-sided switching operation, with Euro profile half cylinder and three keys / with aluminium front plate / right LED red/green, left LED yellow / Operating voltage 24 V DC / Current consumption: 30 mA / IP rating: IP54 / Dimensions: / W x H front plate: 100 x 110 mm / W x H x D flush-mounted housing: approx. 70 x 80 x 48 mm	100064	silver-coloured	100 x 110 x 48 mm	Flush-mounted installation
SCT 222 key switch with LEDs *	Two-sided switching operation, with Euro profile half cylinder and three keys / with aluminium front plate / right LED red/green, left LED yellow / Operating voltage 24 V DC / Current consumption: 30 mA / IP rating: IP54 / Dimensions: / W x H x D: 70 x 80 x 48	100065	silver-coloured	70 x 80 x 48 mm	Surface-mounted installation

\* The products designated above may vary in form, type, characteristics, function, or availability depending on the country. Please get in touch with your GEZE contact person if you have any questions.