Product data sheet

TZ 320 SN stainless steel, flush-mounting set *

Door control unit for controlling escape route doors with key switch and power supply

GEZE GmbH | Reinhold-Vöster-Straße 21–29 | D-71229 Leonberg | **TEL** +49 7152 203-0 | **WEB** www.geze.de | **Mail** info.de@geze.com
2026-11-14T04:13:44Z

TZ 320 SN stainless steel, flush-mounting set *

AREAS OF APPLICATION

- EltVTR-compliant protection of an emergency exit against unauthorised access
- Can be used on single and double leaf doors
- Connectivity via bus enables e.g. interlocking door system control, forwarding of alarms, connection to building management system
- Can be combined with motor locks and swing door drives
- Realisation of a bidirectional emergency exit
- Flush-mounted installation ensures seamless integration into the building

PRODUCT FEATURES

- Flat impact cover enables fast and safe activation of the illuminated emergency push button in panic situations
- Coloured connectors facilitate electrical connection
- Three freely configurable inputs and two freely configurable outputs offer numerous possibilities for additional components
- Number of inputs and outputs can be expanded using the IO 420 interface module or the KL 220 clamping box
- Integrated power supply offers additional flexibility
- Integrated key switch enables authorised passing through the emergency exit
- Robust and attractive stainless steel housing
- Backlighting with LED backlight possible
- Installation in stainless steel box

TECHNICAL DATA

Productname	TZ 320 SN stainless steel, flush-mounting set *
Width	98 mm
Height	260 mm
Depth	70 mm
Type of installation	Flush-mounted installation
Service temperature	-10 - 55 °C
IP rating	IP30
Operating voltage	24 V DC
Current consumption	130 mA
Supply voltage	230 V
Power supply for external consumers (24 V DC)	600 mA
Contact rating	30 V / 1 A
Sabotage contact	Yes

TZ 320 SN stainless steel, flush-mounting set *

Number of inputs	3 Stk.
Number of outputs	2 Stk.
Emergency push button	Yes
Visual display	yes
Volume	75 db
Type of cylinder	Euro profile half cylinder
With ribbon cable	Yes
Parameter setting	Service terminal ST 220
Conforms to the EltVTR (guidelines for electronic locking systems)	Yes
Conforms to EN 13637	No

VARIANTS / ORDER INFO

Designation	Description	Ident-No.	Colour	Dimensions	Operating voltage
TZ 320 SN door control unit, V2A, flush mounting, set *	Consisting of:; Stainless steel front plate flush-mounting, standard; with recess for Euro profile cylinder,; Stainless steel housing flush mounting,; TZ 320 UP control unit; with emergency push button,; SCT 320 key switch,; Emergency exit sign pre-mounted,; SCT design adhesive frame; Power supply 24 V DC / Output current max. 600 mA; Power supply 230 V AC; Operating voltage 24 V DC	155037	Stainless steel	98 x 260 x 70 mm	24 V DC

PART

SCT 320 UP *

Key switch for authorised activation and for changing the mode of operation of automatic doors, flush-mounted

Designation	Description	Ident-No.	Colour	Operating voltage	Type of installation
SCT 320 UP, key switch *	Two-sided switching operation, with Euro profile half cylinder and three keys / with sabotage contact; with ribbon cable; Contact rating: 24 V DC, 1A; Area of application: dry rooms; Without frame	132278	anthracite	24 V DC	Flush-mounted installation
SCT 320 UP, key switch	Two-sided switching operation, with Euro profile half cylinder and three keys / with sabotage contact; with ribbon cable; Contact rating: 24 V DC, 1A; Area of application: dry rooms; Without frame	131984	alpine white	24 V DC	Flush-mounted installation
SCT 320 UP, key switch *	Two-sided switching operation, with Euro profile half cylinder and three keys / with sabotage contact; with ribbon cable; Contact rating: 24 V DC, 1A; Area of application: dry rooms; Without frame	130370	pure white matt	24 V DC	Flush-mounted installation

TZ 320 SN stainless steel, flush-mounting set *

TZ 320 UP CONTROL UNIT *

Door control unit for universally applicable control and protection of networked emergency exits

Designation	Description	Ident-No.	Operating voltage	Type of installation	EAN
TZ 320 UP control unit *	Control unit with emergency push button; Impact cover made of transparent plastic; For switch ranges in System 55; Installation in flush-mounted sockets 62.5 mm deep; Operating voltage: 24 V DC; Current consumption: 100 mA	129586	24 V DC	Flush-mounted installation	4042938295864

POWER SUPPLY NT 1.1 A-24 V UP *

24 V power supply unit for flush-mounted installation

Designation	Description	Ident-No.	Colour	Supply voltage	Dimensions
Power supply NT 1.1 A-24 V UP *	Installation in flush-mounted socket	151426	black	230 V AC	54 x 54 x 32 mm

ACCESSORIES

ST 220

Service terminal for the wireless and wired parameter setting of GEZE door and window products

Designation	Description	Ident-No.	Colour	Dimensions	Operating voltage
Service terminal ST 220	For parameter setting and diagnosis for TZ 320, TE 220, automatic door systems, drives from the IQ windowdrive series and THZ N4, THZ Comfort N4, battery operation with 4x AAA cells (not supplied by GEZE), plain text display on illuminated panel, keypad for operation / Parameter changes to GEZE systems may only be carried out by experts who have been authorised by the manufacturer	087261	blue	80 x 125 x 37 mm	24 V DC

TZ 320 SN stainless steel, flush-mounting set *

RP 220 RELAY BOARD *

Relay board for universal use for the generation and switching of potential-free contacts

Designation	Description	Ident-No.	Dimensions	Number of relays	Supply voltage
RP 220 relay board	For universal use; 2 potential-free change-over contacts; Switching load: 30 V / 1 A; Operating voltage: 24 V DC; Current consumption: 10 mA; W x H x D: 28 x 25 x 18 mm	102355	28 x 25 x 18 mm	2 Stk.	24 V DC

KL 220 AP *

Terminal box for extending the number of analogue inputs and outputs for a TZ 32x

Designation	Description	Ident-No.	Colour	Dimensions	Operating voltage
Terminal box KL 220 surface-mounted installation	Plastic housing; W x H x D: 113 x 113 x 58 mm; IP rating: IP54; with sabotage contact	087262	grey	113 x 113 x 58 mm	24 V DC

SLE 220 *

Warning light for reinforcing an optical alarm signal

Designation	Description	Ident-No.	Colour	Supply voltage	Operating voltage
SLE 220 indicator lamp flush mounting *	Reflector colour: green; Operating voltage: 24 V DC; Switch range: Jung AS 500, alpine white	115936	green	24 V DC	24 V DC
SLE 220 indicator lamp flush mounting *	Reflector colour: red; Operating voltage: 24 V DC; Switch range: Jung AS 500, alpine white	115934	red	24 V DC	24 V DC

TZ 320 SN stainless steel, flush-mounting set *

NOT 320 AP *

RWS emergency push button for opening a sliding or swing door in an emergency

Designation	Description	Ident-No.	Colour	Operating voltage	Type of installation
NOT 320 AP emergency push button, Jung AS 500 *	With AP cap Jung AS 500 and single frame / Impact cover made of transparent plastic; Impact cover dimensions 55 x 55 mm; Operating voltage: 24 V DC; Current consumption: 30 mA; 1 normally closed contact; 1 normally open contact; Contact current capacity: 1A, 30 V	137967	alpine white	24 V DC	Surface-mounted

NOT 220 UP *

RWS emergency push button for switching off the mains voltage in an emergency or during maintenance work, flush-mounted

SCT 222 *

Key switch for authorised activation and changing the mode of operation of automatic doors, surface and flush-mounted

Designation	Description	Ident-No.	Colour	Dimensions	Type of installation
SCT 222 key switch with LEDs *	Two-sided switching operation, with Euro profile half cylinder and three keys / with aluminium front plate; right LED red/green, left LED yellow; Operating voltage 24 V DC; Current consumption: 30 mA; IP rating: IP54; Dimensions:; W x H front plate: 100 x 110 mm; W x H x D flush-mounted housing: approx. 70 x 80 x 48 mm	100064	silver-coloured	100 x 110 x 48 mm	Flush-mounted installation
SCT 222 key switch with LEDs *	Two-sided switching operation, with Euro profile half cylinder and three keys / with aluminium front plate; right LED red/green, left LED yellow; Operating voltage 24 V DC; Current consumption: 30 mA; IP rating: IP54; Dimensions:; W x H x D: 70 x 80 x 48	100065	silver-coloured	70 x 80 x 48 mm	Surface-mounted

TZ 320 SN stainless steel, flush-mounting set *

SCT 320 UP *

Key switch for authorised activation and for changing the mode of operation of automatic doors, flush-mounted

Designation	Description	Ident-No.	Colour	Operating voltage	Type of installation
SCT 320 UP, key switch *	Two-sided switching operation, with Euro profile half cylinder and three keys / with sabotage contact; with ribbon cable; Contact rating: 24 V DC, 1A; Area of application: dry rooms; Without frame	132278	anthracite	24 V DC	Flush-mounted installation
SCT 320 UP, key switch	Two-sided switching operation, with Euro profile half cylinder and three keys / with sabotage contact; with ribbon cable; Contact rating: 24 V DC, 1A; Area of application: dry rooms; Without frame	131984	alpine white	24 V DC	Flush-mounted installation
SCT 320 UP, key switch *	Two-sided switching operation, with Euro profile half cylinder and three keys / with sabotage contact; with ribbon cable; Contact rating: 24 V DC, 1A; Area of application: dry rooms; Without frame	130370	pure white matt	24 V DC	Flush-mounted installation

SCT 220 UP *

Key switch for authorised activation and for changing the mode of operation of automatic doors, flush-mounted

Designation	Description	Ident-No.	Colour	Type of installation	IP rating
SCT 220 key switch, Jung ST 550 *	Two-sided switching operation, with Euro profile half cylinder and three keys / With 1-gang frame	094169	alpine white	Flush-mounted installation	IP20
SCT 220, Jung LS 990 key switch *	Two-sided switching operation, with Euro profile half cylinder and three keys / With Euro profile half cylinder 30/10; ; With single frame; ; IP rating: IP20; ; W x H x D: 81 x 81 x 62.5	094170	Stainless steel	Flush-mounted installation	IP20
SCT 220, GIRA E2 key switch *	Switch range GIRA E2 / With Euro profile half cylinder 30/10; ; With single frame; ; IP rating: IP20; ; W x H x D: 81 x 81 x 62.5	094012	pure white matt	Flush-mounted installation	IP20
SCT 220, Jung LS 990 key switch *	Two-sided switching operation, with Euro profile half cylinder and three keys / With Euro profile half cylinder 30/10; Without frame; IP rating: IP20; W x H x D: 81 x 81 x 62.5	089345	Stainless steel	Flush-mounted installation	IP20

TZ 320 SN stainless steel, flush-mounting set *

T 320 UP CONTROL UNIT *

Slave control unit for bidirectional escape routes with a TZ 320 or TZ 322

Designation	Description	Ident-No.	Operating voltage	Type of installation	EAN
Control unit T 320 flush mounting *	(no complete flush-mounting set available. Made up of individual components) / Control unit with emergency push button; Impact cover made of transparent plastic; For switch ranges in System 55; Installation in flush-mounted sockets 62.5 mm deep; Operating voltage: 24 V DC; Current consumption: 100 mA	140999	24 V DC	Flush-mounted installation	4042938409995

T 320 AP TERMINAL *

Slave control unit for bidirectional escape routes with a TZ 320 or TZ 322 with integrated key switch

Designation	Description	Ident-No.	Colour	Dimensions	Operating voltage
T 320 AP terminal *	Consisting of:; Control unit with emergency push button,; Key switch with Euro profile half cylinder; Emergency exit sign non-illuminated / Operating voltage 24 V DC	141031	green	77 x 197 x 88 mm	24 V DC

* The products designated above may vary in form, type, characteristics, function, or availability depending on the country. Please get in touch with your GEZE contact person if you have any questions.