

Product data sheet

TSA 395 Multi *



Automatic double leaf revolving door system with integrated sliding door

AREAS OF APPLICATION

- Double leaf door systems
- Interior and exterior doors with high access frequency
- Representative building entrances with large incidence of light
- Façades with slim mullion-transom constructions
- Diameters from 3600 up to 5400 mm possible

**PRODUKTBESCHREIBUNG EN**

Note: The product listed may not be available in your country. Please contact your GEZE contact person or send us an e-mail.

PRODUCT FEATURES

- Variable use of the door system as revolving or sliding door
- Extensive additional equipment and surfaces
- Robust and proven drive technology
- Fast commissioning thanks to pre-cabled and configured sensors
- Certification in accordance with EN 16005 (pending)

TECHNICAL DATA

Productname	TSA 395 Multi *
Fully automatic operation	Yes
Inner diameter (min.)	3540 mm
Inner diameter (max.)	5340 mm
Clear passage height	2500 mm
Canopy height (min.)	500 mm
Side elements version	8 mm LSG
Version of roof structure	optical sheet metal covering, waterproof roof with waterspout
Illumination	with roof variant, according to customer wishes
Floor covering	Entrance mat, Entrance mat according to customer wishes
Hot-air curtain system	hot water air curtain, Electric air curtain, installed on top of the suspended ceiling construction
Floor ring	Yes
Disabled person's button	Yes

* The products designated above may vary in form, type, characteristics, function, or availability depending on the country. Please get in touch with your GEZE contact person if you have any questions.