

Product data sheet myGEZE Control output terminal 4-channel relay



Digital output terminal with four potential-free relay outputs and one single contact for each

AREAS OF APPLICATION

- → Connection of non-bus-capable components to the GEZE building system
- → Suitable for signals with a rated voltage of 125 V AC / 30 V DC

GEZE GmbH Reinhold-Vöster-Straße 21–29 D-71229 Leonberg TEL +49 7152 203-0 WEB www.geze.de Mail info.de@geze.com 2024-04-21T14:35:02Z

myGEZE Control output terminal 4-channel relay *



PRODUCT FEATURES

- → Four channels that indicate their signal state through light emitting diodes
- → Four normally open contacts
- → Status LEDs indicate the output status directly

TECHNICAL DATA

Productname	myGEZE Control output terminal 4-channel relay * 12 x 100 x 68 mm -10 - 40 °C Top hat rail mounting	
Dimensions		
Service temperature		
Type of installation		
Switching current	2 A	

VARIANTS / ORDER INFO

Designation	Ident-No.	Dimensions	Type of installation
myGEZE Control 4KRELOUTPUT (201592) *	201592	12 x 100 x 68 mm	Top hat rail mounting

GEZE GmbH Reinhold-Vöster-Straße 21–29 D-71229 Leonberg TEL +49 7152 203-0 WEB www.geze.de Mail info.de@geze.com 2024-04-21T14:35:03Z

^{*} The products designated above may vary in form, type, characteristics, function, or availability depending on the country. Please get in touch with your GEZE contact person if you have any questions.